

View Online at <https://aerobasegroup.com/nsn/4720-00-684-3580>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 0.219 inches and 0.234 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 150.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.625 inches and 0.641 inches

**Minimum Inside Bending Radius:**

3.500 inches

**Exterior Color:**

Blue or black

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

16000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

8000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

18.125 inches and 19.438 inches

**Media For Which Designed:**

Fuel/oil, hydrocarbon and hydraulic fluid single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0