Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-684-3659

C	Cross Sectional Shape:
F	Round
٦	Thread Class:
З	3b 1st end
٦	Thread Direction:
F	Right-hand 1st end
I	nside Diameter:
1	.125 inches
٦	Fempurature Rating:
-	40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
C	Dutside Diameter:
1	.422 inches
C	Connection Style:
S	Swivel nut flare 1st end
E	End Connection Design:
S	Straight 1st end
C	Connection Type:
٦	Fhreaded internal tube 1st end
٦	Fhready Qty Per Inch (tpi):
1	2 1st end
E	Burst Test Pressure:
2	2000.0 pounds per square inch
L	ayer Composition And Location:
C	Duter layer braided steel wire
Ν	Aximum Operating Pressure:
8	300.0 pounds per square inch
٦	Thread Size:
1	.625 inches 1st end
S	Seat Angle:
З	37.0 degrees 1st end
I	nside Surface Condition:
S	Smooth
N	Neasuring Method And Length:
1	9.875 inches working
٦	Thread Series Designator:
ι	Jn 1st end
S	Shelf Life:
٢	√a
ι	Jnit Of Measure:
-	-
0	Demilitarization:
١	No

NSN 4720-00-684-3659

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

