NSN 4720-00-684-4080

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-684-4080

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.625 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response				
Outside Diameter:				
1.078 inches				
Exterior Color:				
Black				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Nuts drilled for lockwire				
Burst Test Pressure:				
6000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord				
Maximum Operating Pressure:				
1500.0 pounds per square inch				
Thread Size:				
1.062 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
3000.0 pounds per square inch				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
24.000 inches working				
Media For Which Designed:				
Fuel/oil, hydrocarbon single response				
Thread Series Designator:				

Unf 1st end

NSN 4720-00-684-4080

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0