
Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-686-8714

Cross Sectional Shape:
Round
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.844 inches
Minimum Inside Bending Radius:
5.000 inches
Flange Outside Diameter:
1.188 inches 2nd end
Connection Style:
Plain w/ gasket groove (sae flanged head) 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Plain face flange 2nd end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
3500.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Cold resistant and mildew resistant and oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
109.000 inches working
Flange Style:
Round w/ out bolt holes 2nd end
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

