## NSN 4720-00-687-8749

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-687-8749

Cross Sectional Shape:
Round
Thread Class:
2b and 2a 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.125 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response
Outside Diameter:
Between 0.470 inches and 0.500 inches
Exterior Color:
Black
Connection Style:
Inverted flare 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal and external tube 2nd end
Thready Qty Per Inch (tpi):
24 and 18 2nd end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated braided cotton cord and 2nd layer rubber impregnated braided cotton cord and outer layer molded rubber
Thread Size:
0.438 inches 1st end
Seat Angle:
30.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
22.625 inches excluding end fittings
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Uns and unf 2nd end
Shelf Life:

N/a

## NSN 4720-00-687-8749

Nonmetallic Hose Assembly - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A542a0