Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-689-8576

| C  | ross Sectional Shape:   |
|----|---|
| R  | ound  |
| TI | hread Class:  |
| 3ł | o 2nd end   |
| TI | hread Direction:  |
| R  | ight-hand 1st end   |
| Т  | empurature Rating:  |
| -6 | 7.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| 0  | utside Diameter:  |
| 0. | 656 inches  |
| A  | ngle Between Rigid Elbow Fittings In Deg:   |
| 0. | 0   |
| С  | onnection Style:  |
| S  | wivel nut flare 2nd end   |
| E  | nd Connection Design:   |
| E  | bow 1st end   |
| С  | onnection Type:   |
| ΤI | nreaded internal tube 2nd end   |
| TI | hready Qty Per Inch (tpi):  |
| 14 | 4 1st end   |
| в  | urst Test Pressure:   |
| 70 | 000.0 pounds per square inch  |
| La | ayer Composition And Location:  |
| 0  | uter layer braided corrosion resistant steel wire                                   |
| Μ  | aximum Operating Pressure:  |
| 15 | 500.0 pounds per square inch  |
| TI | hread Size:   |
| 0. | 875 inches 1st end  |
| S  | eat Angle:  |
| 37 | 7.0 degrees 2nd end   |
| FI | low Angle:  |
| 90 | 0.0 degrees 2nd end   |
| In | side Surface Condition:   |
| S  | mooth   |
| TI | hread Series Designator:  |
| U  | nf 1st end  |
| S  | helf Life:  |
| N  | /a  |
| U  | nit Of Measure:   |
|    |   |
| D  | emilitarization:  |
| N  | 0   |

## NSN 4720-00-689-8576

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

