Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-690-1176

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
0.500 inches	
Tempurature Rating:	
67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Outside Diameter:	
).969 inches	
Minimum Inside Bending Radius:	
7.000 inches	
Connection Style:	
nverted flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external pipe 1st end	
Thready Qty Per Inch (tpi):	
14 1st end	
Burst Test Pressure:	
14000.0 pounds per square inch	
_ayer Composition And Location:	
Ist layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber,	chloroprene
Maximum Operating Pressure:	
3500.0 pounds per square inch	
Thread Size:	
0.500 inches 1st end	
Seat Angle:	
30.0 degrees 1st end	
Hydrostatic Test Pressure:	
7000.0 pounds per square inch	
Duter Covering Environmental Protection:	
Mildew resistant and oil resistant and oil resistant	
nside Surface Condition:	
Smooth	
Measuring Method And Length:	
14.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Fhread Series Designator:	
Jnf 1st end	

NSN 4720-00-690-1176

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

