## NSN 4720-00-690-2615

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-690-2615

Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
Between 0.265 inches and 0.275 inches
Exterior Color:
Black or white
Connection Style:
Swivel nut, compression 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer rubber impregnated fabric
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Hydraulic solution resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
19.875 inches
Seat Radius:
0.031 inches 2nd end
Media For Which Designed:
Hydraulic fluid single response

## NSN 4720-00-690-2615

Nonmetallic Hose Assembly - Page 2 of 2



Inread Series Designator:
Unf 2nd end
Specification Data:
81343-as623 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0