## NSN 4720-00-693-0703

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-693-0703

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.375 inches   |
| Tempurature Rating:  |
| -40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response  |
| Outside Diameter:  |
| 0.750 inches   |
| Connection Style:  |
| Plain 2nd end  |
| End Connection Design:   |
| Straight 2nd end   |
| Connection Type:   |
| Threaded external pipe 2nd end   |
| Thready Qty Per Inch (tpi):  |
| 18 1st end   |
| Burst Test Pressure:   |
| 900.0 pounds per square inch   |
| Layer Composition And Location:  |
| 1st layer braided cotton cord and outer layer molded rubber, synthetic   |
| Maximum Operating Pressure:  |
| 125.0 pounds per square inch   |
| Thread Size:   |
| 0.250 inches 2nd end   |
| Hydrostatic Test Pressure:   |
| 250.0 pounds per square inch   |
| Outer Covering Environmental Protection:   |
| Abrasion resistant and fuel resistant and light resistant and oil resistant and ozone resistant and cold resistant |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 47.125 inches  |
| Media For Which Designed:  |
| Air single response  |
| Thread Series Designator:  |
| Nptf 2nd end   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

## NSN 4720-00-693-0703

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0