## NSN 4720-00-694-4080

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-694-4080

| 00   |
|--|
| Cross Sectional Shape:   |
| Round  |
| Thread Class:  |
| 3b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.375 inches   |
| Outside Diameter:  |
| 0.626 inches   |
| Connection Style:  |
| Swivel nut flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Features Provided:   |
| Reusable end fittings  |
| Burst Test Pressure:   |
| 1000.0 pounds per square inch  |
| Layer Composition And Location:  |
| 1st layer braided cotton cord and outer layer molded rubber, synthetic |
| Maximum Operating Pressure:  |
| 150.0 pounds per square inch   |
| Thread Size:   |
| 0.562 inches 1st end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Hydrostatic Test Pressure:   |
| 300.0 pounds per square inch   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 21.000 inches working  |
| Media For Which Designed:  |
| Air and fuel/oil, hydrocarbon single response                          |
| Thread Series Designator:  |
| Unjf 1st end   |
| Specification Data:  |
| 88044-an6270 government standard                                       |
| Shelf Life:  |

N/a

## NSN 4720-00-694-4080

Nonmetallic Hose Assembly - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A542a0