N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-694-4080

Cross Sectional Shape: Round **Thread Class:** 3b 1st end Thread Direction: Right-hand 1st end **Inside Diameter:** 0.375 inches **Outside Diameter:** 0.626 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 1000.0 pounds per square inch Layer Composition And Location: 1st layer braided cotton cord and outer layer molded rubber, synthetic Maximum Operating Pressure: 150.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 300.0 pounds per square inch **Inside Surface Condition:** Smooth Measuring Method And Length: 21.000 inches working Media For Which Designed: Air and fuel/oil, hydrocarbon single response **Thread Series Designator:** Unjf 1st end **Specification Data:** 88044-an6270 government standard Shelf Life:

NSN 4720-00-694-4080

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0