## NSN 4720-00-694-9910

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-694-9910

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 3b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.312 inches   |
| Tempurature Rating:  |
| -67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response  |
| Outside Diameter:  |
| 0.562 inches   |
| Connection Style:  |
| Swivel nut flare 2nd end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Features Provided:   |
| Electrostatic discharge capability   |
| Burst Test Pressure:   |
| 14000.0 pounds per square inch   |
| Layer Composition And Location:  |
| 1st layer braided steel wire and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided corrosion resistant steel |
| wire   |
| Maximum Operating Pressure:  |
| 3000.0 pounds per square inch  |
| Thread Size:   |
| 0.562 inches 2nd end   |
| Seat Angle:  |
| 37.0 degrees 2nd end   |
| Hydrostatic Test Pressure:   |
| 6000.0 pounds per square inch  |
| Flow Angle:  |
| 45.0 degrees 2nd end   |
| Outer Covering Environmental Protection:   |
| Abrasion resistant   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 23.000 inches working  |

Unf 2nd end

**Thread Series Designator:** 

## NSN 4720-00-694-9910

Nonmetallic Hose Assembly - Page 2 of 2



| _ |     |      |   |        |  |
|---|-----|------|---|--------|--|
| c | hο  | JIF. |   | .ife:  |  |
| J | 116 |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0