NSN 4720-00-696-0195

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-696-0195

Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Connection Style:
Plain 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 1st end
Thready Qty Per Inch (tpi):
27 2nd end
Burst Test Pressure:
1250.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated braided cotton cord and 2nd layer molded rubber and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
625.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
34.000 inches and 34.500 inches
Special Features:
Ferrule on both ends of hose

Fuel/oil, hydrocarbon single response

Media For Which Designed:

NSN 4720-00-696-0195

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0