

View Online at <https://aerobasegroup.com/nsn/4720-00-696-0195>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.438 inches

Connection Style:

Plain 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

27 2nd end

Burst Test Pressure:

1250.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord and 2nd layer molded rubber and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

625.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

34.000 inches and 34.500 inches

Special Features:

Ferrule on both ends of hose

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0