Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-696-0231

<b>Cross Sectional Shape</b>
------------------------------

Round

Thread Class:

2a 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.500 inches

### **Outside Diameter:**

0.719 inches

**Connection Style:** 

Inverted flare 2nd end

#### End Connection Design:

Straight 2nd end

### Connection Type:

Threaded external tube 1st end

## Thready Qty Per Inch (tpi):

18 1st end

### **Burst Test Pressure:**

750.0 pounds per square inch

### Layer Composition And Location:

1st layer braided cotton cord and outer layer molded rubber

## Maximum Operating Pressure:

200.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

45.0 degrees 2nd end

### Hydrostatic Test Pressure:

375.0 pounds per square inch

### **Outer Covering Environmental Protection:**

Mildew resistant and oil resistant and oil resistant and vibration resistant

### Inside Surface Condition:

Smooth

### Measuring Method And Length:

11.125 inches

### **Thread Series Designator:**

Uns 1st end

Shelf Life:

N/a

### Unit Of Measure:

---

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

