

View Online at <https://aerobasegroup.com/nsn/4720-00-698-5140>

**Cross Sectional Shape:**

Round

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.125 inches

**Outside Diameter:**

0.500 inches

**Minimum Inside Bending Radius:**

2.000 inches

**Exterior Color:**

Black

**Connection Style:**

Flared 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting aluminum alloy all ends

**Fitting Component And Surface Treatment:**

Complete fitting anodize 1st end

**Connection Type:**

Threaded external tube 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

5000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

1000.0 pounds per square inch

**Thread Size:**

0.500 inches 1st end

**Seat Angle:**

45.0 degrees 1st end

**Hydrostatic Test Pressure:**

4000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

14.750 inches

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Air single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0