NSN 4720-00-699-7783

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-699-7783

Cross Sectional Shape:
Round
Thread Class:
2b 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.242 inches and 0.273 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
Between 0.594 inches and 0.656 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut with loose or integral clinch sleeve 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 2nd end
Burst Test Pressure:
11000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided steel wire
Maximum Operating Pressure:
2750.0 pounds per square inch
Thread Size:
0.438 inches 2nd end
Seat Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
41.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a

NSN 4720-00-699-7783

Nonmetallic Hose Assembly - Page 2 of 2



	• •						
ın	1+	Of	ΝЛ	ດລ	CI.	ırı	ο.

--

Demilitarization:

No

Fiig:

A542a0