Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-702-6077

Cross Sectional Sh	ano:
Round	ape.
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Tempurature Rating	
	heit and 158.0 degrees fahrenheit single response
Outside Diameter:	
Between 0.812 inche	es and 0.875 inches
Exterior Color:	
Black	
Connection Style:	
Plain optional end 1s	
End Connection De	sign:
Straight 2nd end	
Connection Type:	
Threaded internal pip	
Burst Test Pressure	9:
16000.0 pounds per	
Layer Composition	
1st layer braided stee	el wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene
Maximum Operating	g Pressure:
4000.0 pounds per s	quare inch
Thread Size:	
0.375 inches 1st end	
Hydrostatic Test Pr	essure:
8000.0 pounds per s	quare inch
Outer Covering Env	vironmental Protection:
Abrasion resistant ar	nd light resistant and ozone resistant
Inside Surface Con	dition:
Smooth	
Measuring Method	And Length:
120.000 inches	
Media For Which De	esigned:
Fuel/oil, hydrocarbo	n single response
Thread Series Desig	gnator:
Nptf 2nd end	
Specification Or Sta	andard:
A grade and 3 style a	and 1 type
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0