NSN 4720-00-703-2281

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-703-2281

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
nside Diameter:
0.750 inches
Tempurature Rating:
40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Dutside Diameter:
.250 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
2 1st end
Burst Test Pressure:
2000.0 pounds per square inch
ayer Composition And Location:
st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer braided cotton cord and 4th layer braided steel wire and
outer layer molded rubber, synthetic
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
.062 inches 1st end
Seat Angle:
37.0 degrees 1st end
nside Surface Condition:
Smooth
Measuring Method And Length:
24.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Jn 1st end
Shelf Life:
N/a

--

Unit Of Measure:

NSN 4720-00-703-2281

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0