Nonmetallic Hose Assembly - Page 1 of 2



	uroup
View Online at https://aerobasegroup.com/nsn/4720-00-703-2342	
Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.750 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
1.250 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
12 1st end	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer braided cotton cord and 4th layer b	raided steel wire and
outer layer molded rubber, synthetic	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
1.062 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
9.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Un 1st end	
Shelf Life:	
Unit Of Measure:	

## NSN 4720-00-703-2342

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0