## NSN 4720-00-703-2345



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-703-2345 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.750 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 1.250 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer braided cotton cord and 4th layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 1.062 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant and weatherproof

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

48.000 inches

**Thread Series Designator:** 

Un 1st end

Shelf Life:

N/a

## NSN 4720-00-703-2345

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A542a0