Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-704-9815

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 3b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.188 inches   |
| Tempurature Rating:  |
| -100.0 degrees fahrenheit and 450.0 degrees fahrenheit single response                                   |
| Outside Diameter:  |
| 0.312 inches   |
| Minimum Inside Bending Radius:   |
| 2.000 inches   |
| First End Fitting Specification/std Data:  |
| An818-4 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Connection Style:  |
| Swivel nut flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| End Fitting Component And Material:  |
| Socket steel all ends  |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Second End Relationship With First End:  |
| Identical  |
| Burst Test Pressure:   |
| 12000.0 pounds per square inch   |
| First End Swivel Action Capability:  |
| Not included   |
| Maximum Operating Pressure:  |
| 1000.0 pounds per square inch  |
| Thread Size:   |
| 0.438 inches 1st end   |
| Seat Angle:  |
| 45.0 degrees 1st end   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 55.000 inches  |
| Special Features:  |
| Inner conveying tube material-plastic, polytetrafluoroethylene   |



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Specification Data:

An818-4 national std/spec

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0