NSN 4720-00-705-7868

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-705-7868

Cross Sectional Shape:
Round
Inside Diameter:
1.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Flange Thickness:
0.495 inches 2nd end
Outside Diameter:
1.812 inches
Minimum Inside Bending Radius:
16.000 inches
Angle Between Rigid Elbow Fittings In Deg:
90.0
Flange Outside Diameter:
2.000 inches 2nd end
Connection Style:
Plain w/ gasket groove (sae flanged head) 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Plain face flange 2nd end
Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
625.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
138.000 inches
Flange Style:
Round w/ out bolt holes 2nd end
Shelf Life:
N/a

N/a

NSN 4720-00-705-7868

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0