NSN 4720-00-705-9028

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-705-9028

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.250 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting cadmium 1st end
Connection Type:
Threaded external pipe 1st end
Thready Qty Per Inch (tpi):
14 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
12000.0 pounds per square inch
12000.0 pounds per square inch First End Swivel Action Capability:
·
First End Swivel Action Capability:
First End Swivel Action Capability: Not included
First End Swivel Action Capability: Not included Layer Composition And Location:
First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer spirally laid steel wire
First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer spirally laid steel wire Maximum Operating Pressure:
First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer spirally laid steel wire Maximum Operating Pressure: 300.0 pounds per square inch
First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer spirally laid steel wire Maximum Operating Pressure: 300.0 pounds per square inch Thread Size:
First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer spirally laid steel wire Maximum Operating Pressure: 300.0 pounds per square inch Thread Size: 0.750 inches 1st end
First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer spirally laid steel wire Maximum Operating Pressure: 300.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle:
First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer spirally laid steel wire Maximum Operating Pressure: 300.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end
First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer spirally laid steel wire Maximum Operating Pressure: 300.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure:
First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer spirally laid steel wire Maximum Operating Pressure: 300.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 600.0 pounds per square inch
First End Swivel Action Capability: Not included Layer Composition And Location: 2nd layer spirally laid steel wire Maximum Operating Pressure: 300.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 600.0 pounds per square inch Outer Covering Environmental Protection:

NSN 4720-00-705-9028

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 17.500 inches Special Features: Inner conveying tube material-rubber, synthetic Media For Which Designed: Hydraulic fluid single response Thread Series Designator: Nptf 1st end Shelf Life: N/a Unit Of Measure: -Demilitarization:

No Fiig: A542a0