NSN 4720-00-705-9542

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-705-9542

Cross Sectional Shape:
Round
Inside Diameter:
4.000 inches
Tempurature Rating:
-32.0 degrees celsius and 52.0 degrees celsius single response
Outside Diameter:
4.750 inches
Exterior Color:
Black
Quick Disconnect Size:
4.000 inches 2nd end
Connection Style:
Cam or lever (external) 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Internal quick disconnect 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
500.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated braided cotton cord and 2nd layer spirally wrapped steel fabric and outer layer molded rubber, synthetic
Hydrostatic Test Pressure:
150.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and fuel resistant and oil resistant and ozone resistant and water resistant and salt water resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
300.000 inches excluding end fittings
Special Features:
Female end supplied w/one ms27030-9 gasket and one ms27029-17 dust plug
Special Markings:
Liquid fuel
Specification Data:
81349-mil-prf-370 government specification
Specification Or Standard:
9 size
Shelf Life:

NSN 4720-00-705-9542

Nonmetallic Hose Assembly - Page 2 of 2



H	nii	: Of	M	226	ur	Δ.
v		. 0	1414	-u3	uı	С.

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-prf-370 spec.