NSN 4720-00-705-9560



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-705-9560 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.406 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.766 inches **Connection Style:** Swivel nut, flareless 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and 2nd layer braided cotton cord and 3rd layer braided steel wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 12.0 degrees 1st end **Hydrostatic Test Pressure:** 4000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 23.375 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:**

N/a
Unit Of Measure:

Unf 1st end Shelf Life:

NSN 4720-00-705-9560

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0