NSN 4720-00-706-2230

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-706-2230

View Online at https://aerobasegroup.com/nsn/4720-00-706-2230
Cross Sectional Shape:
Round
Inside Diameter:
3.000 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Flange Thickness:
0.360 inches and 0.370 inches 2nd end
Outside Diameter:
3.625 inches
Minimum Inside Bending Radius:
18.000 inches
Flange Outside Diameter:
4.000 inches 2nd end
Connection Style:
Plain w/ gasket groove (sae flanged head) 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Plain face flange 2nd end
Burst Test Pressure:
225.0 pounds per square inch
Layer Composition And Location:
1st layer woven cotton with interwoven steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
55.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
23.625 inches
Flange Style:
Round w/ out bolt holes 2nd end
Media For Which Designed:
Hydraulic fluid, water base single response

Shelf Life:

N/a

NSN 4720-00-706-2230

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0