## NSN 4720-00-706-5169

**Cross Sectional Shape:** 

Round

**Thread Class:** 

Unf 2nd end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-706-5169

3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.562 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
outer layer braided correction recitating close wife
Maximum Operating Pressure:
Maximum Operating Pressure:
Maximum Operating Pressure: 1500.0 pounds per square inch
Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size:
Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.750 inches 2nd end
Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle:
Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.750 inches 2nd end  Seat Angle:  37.0 degrees 2nd end
Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.750 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:
Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.750 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch
Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.750 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:
Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.750 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:  90.0 degrees 2nd end
Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.750 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:  90.0 degrees 2nd end  Inside Surface Condition:
Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.750 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:  90.0 degrees 2nd end  Inside Surface Condition:  Smooth
Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.750 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:  90.0 degrees 2nd end  Inside Surface Condition:  Smooth  Measuring Method And Length:
Maximum Operating Pressure:  1500.0 pounds per square inch  Thread Size:  0.750 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:  90.0 degrees 2nd end  Inside Surface Condition:  Smooth  Measuring Method And Length:  25.000 inches working

## NSN 4720-00-706-5169

Nonmetallic Hose Assembly - Page 2 of 2



Specific	cation	Data:
----------	--------	-------

07482-102a138+0802500 manufacturers source control

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0