Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-706-6828

| ~  | reas Sectional Chanas   |
|----|---|
|    | ross Sectional Shape:   |
|    | ound  |
|    | hread Class:  |
|    | a 1st end   |
|    | hread Direction:  |
|    | ight-hand 1st end   |
|    | side Diameter:  |
| -  | 188 inches  |
|    | empurature Rating:  |
|    | 5.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| 0  | utside Diameter:  |
| 0. | 312 inches  |
| Μ  | inimum Inside Bending Radius:   |
| 3. | 000 inches  |
| C  | onnection Style:  |
| FI | ared 1st end  |
| E  | nd Connection Design:   |
| S  | traight 1st end   |
| C  | onnection Type:   |
| Tł | nreaded external tube 1st end   |
| Fe | eatures Provided:   |
| E  | ectrostatic discharge capability  |
| B  | urst Test Pressure:   |
| 12 | 2000.0 pounds per square inch   |
| La | ayer Composition And Location:  |
| 0  | uter layer braided corrosion resistant steel wire                                   |
| Μ  | aximum Operating Pressure:  |
| 15 | 500.0 pounds per square inch  |
| T  | hread Size:   |
| 0. | 438 inches 1st end  |
| S  | eat Angle:  |
| 37 | 7.0 degrees 1st end   |
| H  | ydrostatic Test Pressure:   |
| 30 | 000.0 pounds per square inch  |
| V  | acuum In Torr:  |
| 50 | 0.8   |
| In | side Surface Condition:   |
| S  | mooth   |
| М  | easuring Method And Length:   |
|    | 875 inches working  |
|    | hread Series Designator:  |
|    | nf 1st end  |

## NSN 4720-00-706-6828

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

