## NSN 4720-00-706-6835

**Cross Sectional Shape:** 

Round

Thread Class: 3a 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-706-6835

| Thread Direction:   |
|---|
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.188 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.312 inches  |
| Minimum Inside Bending Radius:  |
| 2.000 inches  |
| Exterior Color:   |
| Natural   |
| Connection Style:   |
| Flared 2nd end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded external tube 2nd end  |
| Features Provided:  |
| Electrostatic discharge capability  |
| Burst Test Pressure:  |
| 12000.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire                                    |
| Maximum Operating Pressure:   |
| 1500.0 pounds per square inch   |
| Thread Size:  |
| 0.438 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 2nd end  |
| Hydrostatic Test Pressure:  |
| 3000.0 pounds per square inch   |
| Flow Angle:   |
| 45.0 degrees 2nd end  |
| Vacuum In Torr:   |
| 50.8  |
| Inside Surface Condition:   |
| Smooth  |

## NSN 4720-00-706-6835

Nonmetallic Hose Assembly - Page 2 of 2



| weasaring wethou And Length. | Measuring | Method | And | Length: |
|------------------------------|-----------|--------|-----|---------|
|------------------------------|-----------|--------|-----|---------|

9.750 inches working

**Thread Series Designator:** 

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0