NSN 4720-00-706-6836

Cross Sectional Shape:

Round

Thread Class: 3a 1st end

Thread Direction:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-706-6836

Right-hand 1st end			
Inside Diameter:			
0.312 inches			
Tempurature Rating:			
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response			
Outside Diameter:			
0.438 inches			
Minimum Inside Bending Radius:			
4.000 inches			
Exterior Color:			
Natural			
Connection Style:			
Flared 2nd end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded external tube 2nd end			
Features Provided:			
Electrostatic discharge capability			
Burst Test Pressure:			
9000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
1500.0 pounds per square inch			
Thread Size:			
0.562 inches 1st end			
Seat Angle:			
37.0 degrees 2nd end			
Hydrostatic Test Pressure:			
3000.0 pounds per square inch			
Flow Angle:			
45.0 degrees 2nd end			
Vacuum In Torr:			
50.8			
Inside Surface Condition:			
Smooth			

NSN 4720-00-706-6836

Nonmetallic Hose Assembly - Page 2 of 2



Measuring	Method	And	Length:

9.750 inches working

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A542a0