Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-706-9087

cross Sectional Shape:	
tound	
hread Direction:	
light-hand 1st end	
nside Diameter:	
.750 inches	
empurature Rating:	
67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Dutside Diameter:	
.250 inches	
Connection Style:	
nverted flare 1st end	
nd Connection Design:	
traight 1st end	
Connection Type:	
hreaded external pipe 1st end	
hready Qty Per Inch (tpi):	
4 1st end	
Burst Test Pressure:	
000.0 pounds per square inch	
ayer Composition And Location:	
st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber	, chloroprene
laximum Operating Pressure:	
250.0 pounds per square inch	
hread Size:	
.750 inches 1st end	
eat Angle:	
0.0 degrees 1st end	
lydrostatic Test Pressure:	
500.0 pounds per square inch	
Outer Covering Environmental Protection:	
lildew resistant and oil resistant and oil resistant	
nside Surface Condition:	
mooth	
leasuring Method And Length:	
1.500 inches	
ledia For Which Designed:	
uel/oil, hydrocarbon single response	
hread Series Designator:	
Inf 1st end	
shelf Life:	
l/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0