Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-706-9092

	Cross Sectional Shape:
	Round
	Thread Direction:
	Right-hand 1st end
I	nside Diameter:
(0.500 inches
٦	Tempurature Rating:
-	65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
(Dutside Diameter:
(0.969 inches
ľ	Minimum Inside Bending Radius:
7	7.000 inches
(Connection Style:
F	Plain 1st end
E	End Connection Design:
S	Straight 1st end
(Connection Type:
٦	Threaded external pipe 1st end
E	Burst Test Pressure:
1	4000.0 pounds per square inch
L	ayer Composition And Location:
1	st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene
	Maximum Operating Pressure:
3	3000.0 pounds per square inch
٦	Thread Size:
(0.500 inches 1st end
Ş	Seat Angle:
3	30.0 degrees 1st end
ł	Hydrostatic Test Pressure:
7	7000.0 pounds per square inch
C	Duter Covering Environmental Protection:
ſ	Aildew resistant and oil resistant and oil resistant
I	nside Surface Condition:
ę	Smooth
ľ	Measuring Method And Length:
2	16.000 inches
ľ	Media For Which Designed:
F	Fuel/oil, hydrocarbon single response
٦	Thread Series Designator:
١	Nptf 1st end
ę	Shelf Life:
1	N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0