## NSN 4720-00-706-9095

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-706-9095

Cross Sastianal Shana						
Cross Sectional Shape: Round						
Thread Direction:						
Right-hand 1st end  Inside Diameter:						
0.500 inches						
empurature Rating:						
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response						
Outside Diameter: 0.969 inches						
Minimum Inside Bending Radius:						
7.000 inches						
Connection Style:						
Plain 1st end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded external pipe 1st end						
Burst Test Pressure:						
14000.0 pounds per square inch						
_ayer Composition And Location:						
st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene						
Maximum Operating Pressure:						
3000.0 pounds per square inch						
Thread Size:						
0.500 inches 1st end						
Seat Angle:						
30.0 degrees 1st end						
Hydrostatic Test Pressure:						
7000.0 pounds per square inch						
Outer Covering Environmental Protection:						
Mildew resistant and oil resistant and oil resistant						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
70.000 inches						
Media For Which Designed:						
Fuel/oil, hydrocarbon single response						
Thread Series Designator:						
Nptf 1st end						
Shelf Life:						
Offer Life.						

N/a

## NSN 4720-00-706-9095

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A542a0