## NSN 4720-00-706-9109



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-706-9109 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.844 inches **Minimum Inside Bending Radius:** 5.000 inches **Connection Style:** Inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Burst Test Pressure:** 16000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 3500.0 pounds per square inch **Thread Size:** 0.375 inches 1st end **Hydrostatic Test Pressure:** 8000.0 pounds per square inch **Outer Covering Environmental Protection:** Mildew resistant and oil resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 60.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** 

N/a
Unit Of Measure:

Nptf 1st end Shelf Life:

## NSN 4720-00-706-9109

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0