Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-706-9113

	Cross Sectional Shape:
	Round
	Thread Direction:
	Right-hand 1st end
	nside Diameter:
).375 inches
٦	Tempurature Rating:
-	65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
(Dutside Diameter:
(0.844 inches
ľ	Minimum Inside Bending Radius:
5	5.000 inches
(Connection Style:
I	nverted flare 1st end
E	End Connection Design:
S	Straight 1st end
(Connection Type:
٦	Threaded external pipe 1st end
٦	Thready Qty Per Inch (tpi):
1	18 1st end
E	Burst Test Pressure:
1	6000.0 pounds per square inch
L	ayer Composition And Location:
1	Ist layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene
ľ	Maximum Operating Pressure:
3	3500.0 pounds per square inch
٦	Thread Size:
(0.375 inches 1st end
ł	Hydrostatic Test Pressure:
8	3000.0 pounds per square inch
(Duter Covering Environmental Protection:
ľ	Aildew resistant and oil resistant and oil resistant
I	nside Surface Condition:
S	Smooth
ľ	Measuring Method And Length:
2	203.000 inches
ľ	Media For Which Designed:
F	Fuel/oil, hydrocarbon single response
٦	Thread Series Designator:
١	Nptf 1st end
ę	Shelf Life:
1	N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0