

View Online at <https://aerobasegroup.com/nsn/4720-00-706-9125>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 0.242 inches and 0.273 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.656 inches and 0.718 inches

**Minimum Inside Bending Radius:**

4.000 inches

**End Application:**

Nsn2350-00-122-6826, m88a1

**Connection Style:**

Plain 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external pipe 1st end

**Thready Qty Per Inch (tpi):**

18 1st end

**Burst Test Pressure:**

20000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

5000.0 pounds per square inch

**Thread Size:**

0.250 inches 1st end

**Hydrostatic Test Pressure:**

10000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Hydraulic solution resistant and mildew resistant and ozone resistant and cold resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

23.750 inches and 24.250 inches

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Nptf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0