

View Online at <https://aerobasegroup.com/nsn/4720-00-706-9128>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.485 inches and 0.531 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

Between 0.875 inches and 0.937 inches

Minimum Inside Bending Radius:

7.000 inches

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external pipe 1st end

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and outer layer molded rubber, chloroprene

Maximum Operating Pressure:

2000.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

4000.0 pounds per square inch

Outer Covering Environmental Protection:

Hydraulic solution resistant and mildew resistant and ozone resistant and cold resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

59.500 inches and 60.500 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0