NSN 4720-00-706-9130

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-706-9130

Round				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.250 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response				
Outside Diameter:				
0.625 inches				
Minimum Inside Bending Radius:				
4.000 inches				
End Application:				
M578 recovery rehicle				
Connection Style:				
Inverted flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded external pipe 1st end				
Thready Qty Per Inch (tpi):				
18 1st end				
Burst Test Pressure:				
11000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided steel wire and outer layer molded rubber, synthetic				
Maximum Operating Pressure:				
2750.0 pounds per square inch				
Thread Size:				
0.250 inches 1st end				
Seat Angle:				
30.0 degrees 1st end				
Hydrostatic Test Pressure:				
5500.0 pounds per square inch				
Outer Covering Environmental Protection:				
Corrosion resistant and oil resistant and weatherproof and hydraulic solution resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
46.000 inches				
Media For Which Designed:				
Fuel/oil, hydrocarbon single response				

NSN 4720-00-706-9130

Nonmetallic Hose Assembly - Page 2 of 2



		•		
Ιh	read	Series	Desiar	າator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0