Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobase	group.com/nsn/4720-00-706-9162
Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.313 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 1	60.0 degrees fahrenheit single response
Outside Diameter:	
0.672 inches	
Connection Style:	
Inverted flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external pipe 1st end	
Thready Qty Per Inch (tpi):	
18 1st end	
Burst Test Pressure:	
9000.0 pounds per square inch	
Layer Composition And Loca	tion:
1st layer braided cotton cord an	d 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure	•
2000.0 pounds per square inch	
Thread Size:	
0.375 inches 1st end	
Seat Angle:	
30.0 degrees 1st end	
Hydrostatic Test Pressure:	
4500.0 pounds per square inch	
Outer Covering Environmenta	al Protection:
Fire retardant and hydraulic sol	ution resistant and mildew resistant and oil resistant
Inside Surface Condition:	
Smooth	
Measuring Method And Lengt	h:
222.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single res	sponse
Thread Series Designator:	
Nptf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0