

View Online at <https://aerobasegroup.com/nsn/4720-00-707-1214>

Cross Sectional Shape:

Round

Inside Diameter:

1.250 inches

Temperature Rating:

-65.0 degrees fahrenheit single response

Flange Thickness:

0.310 inches and 0.320 inches 1st end

Outside Diameter:

2.000 inches

Minimum Inside Bending Radius:

16.000 inches

Angle Between Rigid Elbow Fittings In Deg:

12.0

Flange Outside Diameter:

1.990 inches and 2.010 inches 1st end

Connection Style:

Plain w/ gasket groove (sae flanged head) 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Plain face flange 1st end

Burst Test Pressure:

6500.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and 2nd layer braided steel wire and 3rd layer braided textile yarn and outer layer molded rubber, synthetic

Maximum Operating Pressure:

1625.0 pounds per square inch

Hydrostatic Test Pressure:

3250.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

39.500 inches working

Flange Style:

Round w/ out bolt holes 1st end

Special Features:

One end has two 90 degrees bends in tube

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0