

View Online at <https://aerobasegroup.com/nsn/4720-00-707-5952>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.906 inches

Minimum Inside Bending Radius:

7.000 inches

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external tube 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and 2nd layer braided cotton cord and outer layer molded rubber

Maximum Operating Pressure:

2000.0 pounds per square inch

Thread Size:

0.875 inches 1st end

Seat Angle:

45.0 degrees 1st end

Outer Covering Environmental Protection:

Abrasion resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

26.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0