NSN 4720-00-708-5394

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-708-5394

Cross Sectional Shape:					
Round					
Thread Class:					
3b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.875 inches					
Tempurature Rating:					
-67.0 degrees fahrenheit and 450.0 degrees fahrenheit single response					
Outside Diameter:					
1.109 inches					
Connection Style:					
Swivel nut flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Thready Qty Per Inch (tpi):					
12 1st end					
Burst Test Pressure:					
3500.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire					
Maximum Operating Pressure:					
1250.0 pounds per square inch					
Thread Size:					
1.312 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
2500.0 pounds per square inch					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
50.000 inches working					
Thread Series Designator:					
Un 1st end					
Specification Data:					
81349-mil-h-25579 government specification					
Shelf Life:					

N/a

NSN 4720-00-708-5394

Nonmetallic Hose Assembly - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-25579 spec.