Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-709-0356

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-100.0 degrees fahrenheit and 500.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and outer layer molded polytetrafluoroethylene
Maximum Operating Pressure:
2500.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
12.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
13.000 inches
Special Features:
Aluminum identification sleeve on hose
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

