## NSN 4720-00-710-4421

**Cross Sectional Shape:** 

Round

Smooth

Thread Class: 3b 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-710-4421

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.781 inches
Minimum Inside Bending Radius:
6.500 inches
Exterior Color:
Natural
Connection Style:
Swivel nut with compression sleeve 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:

## NSN 4720-00-710-4421

Nonmetallic Hose Assembly - Page 2 of 2



## Measuring Method And Length: 21.375 inches working Thread Series Designator: Un 1st end Specification Data: 81349-mil-h-25579 government specification Specification Or Standard: 1 class and 12 size Shelf Life: N/a Unit Of Measure: -Demilitarization: No Fiig:

A542a0

Mil-std (military Standard):

Mil-h-25579 spec.