NSN 4720-00-711-3496

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-711-3496

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.620 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.910 inches |
| Minimum Inside Bending Radius: |
| 6.500 inches |
| Angle Between Rigid Elbow Fittings In Deg: |
| 120.0 |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Elbow 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 2 2nd end |
| Burst Test Pressure: |
| 1000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided steel wire |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch |
| Thread Size: |
| 1.062 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 500.0 pounds per square inch |
| Flow Angle: |
| 45.0 degrees 1st end |
| Vacuum In Torr: |
| 50.8 |

Smooth

Inside Surface Condition:

NSN 4720-00-711-3496

Nonmetallic Hose Assembly - Page 2 of 2



| Measuring | Method | And | Length: |
|-----------|--------|-----|---------|
| | | | |

11.000 inches working

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0