Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-712-1306

Cross Se	ectional Shape:
Round	
Inside D	iameter:
0.380 inc	hes
Tempura	ature Rating:
-40.0 deg	rees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside	Diameter:
0.620 inc	hes
Minimun	n Inside Bending Radius:
3.000 inc	hes
End Con	nection Design:
Straight 1	Ist end
Connect	ion Type:
Unthread	led external tube 1st end
Burst Te	st Pressure:
1000.0 p	ounds per square inch
Layer Co	omposition And Location:
Outer lay	er braided cotton cord
Maximur	n Operating Pressure:
250.0 po	unds per square inch
Hydrosta	atic Test Pressure:
500.0 po	unds per square inch
Outer Co	overing Environmental Protection:
Mildew re	esistant and oil resistant
Vacuum	In Torr:
50.8	
Inside S	urface Condition:
Smooth	
Measurii	ng Method And Length:
7.500 inc	hes
Outside	Diameter Tube Accommodated:
0.370 inc	hes 1st end
Shelf Lif	e:
N/a	
Unit Of M	Neasure:
Demilita	rization:
No	
Fiig:	
A542a0	