NSN 4720-00-713-5710

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-713-5710

Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Complete fitting copper alloy all ends
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
20 1st end
Second End Relationship With First End:
Not identical
THE THE THE STATE OF THE STATE
Burst Test Pressure:
Burst Test Pressure:
Burst Test Pressure: 700.0 pounds per square inch
Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability:
Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included
Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location:
Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic
Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size:
Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.562 inches 1st end
Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.562 inches 1st end Seat Angle:
Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.562 inches 1st end Seat Angle: 30.0 degrees 1st end
Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.562 inches 1st end Seat Angle: 30.0 degrees 1st end Outer Covering Environmental Protection:
Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.562 inches 1st end Seat Angle: 30.0 degrees 1st end Outer Covering Environmental Protection: Oil resistant and ozone resistant

Not included

17.250 inches

Second End Swivel Action Capability:

NSN 4720-00-713-5710

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:
Inner conveying tube material-rubber, synthetic
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0