NSN 4720-00-713-5710

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-713-5710

| Round |
|--|
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.188 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.438 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 2nd end |
| End Fitting Component And Material: |
| Complete fitting copper alloy all ends |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 20 1st end |
| |
| Second End Relationship With First End: |
| Second End Relationship With First End: Not identical |
| · |
| Not identical |
| Not identical Burst Test Pressure: |
| Not identical Burst Test Pressure: 700.0 pounds per square inch |
| Not identical Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: |
| Not identical Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included |
| Not identical Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: |
| Not identical Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic |
| Not identical Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: |
| Not identical Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.562 inches 1st end |
| Not identical Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.562 inches 1st end Seat Angle: |
| Not identical Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.562 inches 1st end Seat Angle: 30.0 degrees 1st end |
| Not identical Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.562 inches 1st end Seat Angle: 30.0 degrees 1st end Outer Covering Environmental Protection: |
| Not identical Burst Test Pressure: 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber, synthetic Thread Size: 0.562 inches 1st end Seat Angle: 30.0 degrees 1st end Outer Covering Environmental Protection: Oil resistant and ozone resistant |

Not included

17.250 inches

Second End Swivel Action Capability:

NSN 4720-00-713-5710

Nonmetallic Hose Assembly - Page 2 of 2



| Special Features: |
|---|
| Inner conveying tube material-rubber, synthetic |
| Media For Which Designed: |
| Hydraulic fluid single response |
| Thread Series Designator: |
| Un 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A542a0