Nonmetallic Hose Assembly - Page 1 of 2

**ACTUBA** Gro

View Online at https://aerobasegroup.com/nsn/4720-00-715-1560

#### **Cross Sectional Shape:**

Round

**Inside Diameter:** 

4.000 inches

# **Tempurature Rating:**

-32.0 degrees celsius and 52.0 degrees celsius single response

#### Outside Diameter:

4.750 inches

**Exterior Color:** 

Black

#### **Quick Disconnect Size:**

4.000 inches 2nd end

#### **Connection Style:**

Cam or lever (external) 2nd end

#### End Connection Design:

Straight 2nd end

#### **Connection Type:**

Internal quick disconnect 1st end

#### Features Provided:

Electrostatic discharge capability

#### **Burst Test Pressure:**

500.0 pounds per square inch

#### Layer Composition And Location:

1st layer rubber impregnated braided cotton cord and 2nd layer spirally wrapped steel fabric and outer layer molded rubber, synthetic

#### Hydrostatic Test Pressure:

150.0 pounds per square inch

#### **Outer Covering Environmental Protection:**

Fuel resistant and oil resistant and mildew resistant and solvent resistant

### Inside Surface Condition:

Smooth

# Measuring Method And Length:

180.000 inches excluding end fittings

## **Special Markings:**

Liquid fuel

# Specification Data:

81349-mil-h-370 government specification

# Specification Or Standard:

B type and 9 size and b class and 1 style

# Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 4720-00-715-1560

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-370 spec.